

strapex

Stand alone, mobile machines for plastic strapping



SMA 10



SMA 20



SMG 10

Simple solutions

For shipping departments with small to medium volume of packages

Model SMA 20

User friendly machine for various applications

Adjustable table height from 700–830 mm

Accurately adjustable strap tension from 5–450 N

Use of Polypropylene strap, widths from 9/12 mm

Fast and easy coil change

Mounted on castors and single phase electrical supply, affords maximum mobility



Simple to operate with fast strapping speed

Cycle starts automatically when strap is inserted



Versatile

For the daily shipping of single or collective packages. Also protects against pilferage.



Easy to maintain and energy saving

Automatic motor shut off after each cycle



Clearly arranged control panel

No overhanging operating functions



Model SMA 10

Economical alternative for shipping departments with small volume of packages



Model SMG 10

High performance machine with 5 highlights

- Up to 70 cycles per minute
- Touch Panel: Strap tension easily adjustable
- Simple technology, few moving parts
- Constant strap tension for various products
- Simple coil change

Technical data	SMA 10	SMA 20	SMG 10
----------------	--------	--------	--------

Article number	351.530.001	351.400.001	740.120.101 740.120.121
----------------	-------------	-------------	----------------------------

Machines

Machine dimension			
– Width x depth	900 x 600 mm	870 x 500 mm	900 x 615 mm
– Table height	700 – 920 mm	700 – 830 mm	770 – 930 mm
– Arch dimension (W x H)		740.120.101: 740.120.121:	500 x 400 mm 650 x 500 mm

Weight	81 kg	68 kg	170 kg
Electrical supply	230 V, 50 Hz 115 V, 60 Hz	230 V, 50 Hz 115 V, 60 Hz	230 V, 50 Hz 115 V, 60 Hz
Power consumption	0.77 kW	0.3 kW	0.52 kW

Tensioning force, fully adjustable	60 – 450 N	5 – 450 N	300 N
Speed cycles per minute, max.	12	15	70

Cycle start			
– Automatically when strap is inserted	•	•	
– Foot switch		•	•
– Manually (push button)	•		
Heat seal	•	•	•

Plastic strap

Quality	Polypropylene (PP)	Polypropylene (PP)	Polypropylene (PP)
Width	9/12 mm	9/12 mm	5 mm
Thickness	0,45 – 0,75 mm	0,45 – 0,75 mm	0,35 – 0,60 mm
Core size, Ø	200 mm	200 mm	200 mm

Min. packaging size

Width x height, approx.	50 x 30 mm	45 x 20 mm	100 x 20 mm
-------------------------	------------	------------	-------------

Options

Second pedal	•
Package stop plate	•
Table trigger with light barrier	•



Strap tension adjustable with press button



Simple coil change

Make your products feel safe



Own development and manufacturing



Proven solutions for various industry segments



Worldwide sales and service network

www.strapex.com