

strapex

SMG 10/15/25

High performance machines for plastic strapping



SMG 10/15



SMG 25



New technology allows use of thin or narrow strap



Save time and money with 5 mm plastic strap!

SMG 10/15/25

For small to large packages

5 Highlights

- Up to 70 cycles per minute
- Touch Panel: Strap tension easily adjustable
- Simple technology, few moving parts
- Constant strap tension for various products
- Simple coil change

Cost effective

- High availability
- Use of 5 mm PP strap with SMG 10 – the alternative to 9/12 mm strap
- Use of thin PP straps
- Maintenance-friendly

Strapex advantage



Machine, strap and after-sales service as a total package



User friendly

- Plug & Play: Very easy handling
- Mobile, ready to use anywhere
- Adjustable working height
- All operating functions using foot pedal



Strap tension easily adjustable with press button



Simple coil change



Easily accessible



Maintenance without tools



Robust, compact design

Technical data	SMG 10	SMG 15	SMG 25
Dispenser position	Integrated	Integrated	Side mounted
Performance per minute	70 cycles	70 cycles	70 cycles
Arch dimensions (width x height)			
– 500 x 400 mm	5 mm		
– 650 x 500 mm	5 mm	9/12 mm	
– 850 x 650 mm			9/12 mm
– 850 x 850 mm			9/12 mm
– 1250 x 500 mm			9/12 mm
– 1250 x 850 mm			9/12 mm
– 1550 x 500 mm			9/12 mm
Working height	770–930 mm	770–930 mm	670–930 mm
Electrical supply	230 V, 50 Hz	230 V, 50 Hz	230 V, 50 Hz
	115 V, 60 Hz	115 V, 60 Hz	115 V, 60 Hz
Strap tension, up to	300 N	450 N	450 N
Seal	30 s	30 s	30 s
Weight, approx.	170 kg	170 kg	190 kg
Plastic strap (PP)			
Width 5 mm	372.605.585		
9 mm		371.609.545	371.609.545
12 mm		371.612.533	371.612.533
Strap coil, inside/outside Ø	200/430 mm	200/430 mm	200/430 mm
Packages			
Min. width / Max. weight	100 mm / 35 kg	100 mm / 35 kg	100 mm / 35 kg

Make your products feel safe

Options



Second foot pedal for operation on both sides



Cycle start triggered by photocell



Roller table for easy handling of heavy parcels



Bundle stops for precise positioning of loose packages

Further options

- Foot switch with protection cover
- Hold down device for compressing loose packages
- Interface for integration into existing production plants